



Power Generation

Challenge

Protecting sub-stations, electrical switch rooms, control rooms, data communications and other critical areas where the requirement is for multiple hazards with centrally stored FM-200 containers and selector valves.

Solution

HYGOOD FM-200 Piston Flow Clean Agent Fire Suppression System

Application

Fire suppression for critical operational infrastructure in cramped conditions

Power stations and power generation facilities incorporate a wide range of critical and ancillary services and buildings to ensure continued operations and plant uptime. Away from the primary power circuit, boiler and turbine system; vital facilities such as sub-stations, cable voids, control rooms, data communications and backup systems must be effectively protected against fire risk. Selecting the right solution to help protect this critical plant infrastructure is key.

The HYGOOD FM-200* Piston Flow Clean Agent Fire Suppression System has zero ozone depletion potential (ODP). The system uses FM-200 (HFC-227ea) fire extinguishant which vaporizes upon discharge and absorbs heat to rapidly suppress fire. Rapid fire suppression can result in less damage to critical equipment, facilitating a much shorter recovery time and reducing downtime. Safe for use in occupied areas at the design concentration, the system helps protect critical infrastructure of power generation facilities.

The HYGOOD FM-200 Piston Flow Clean Agent Fire Suppression System is the most effective when used with the automatic Detection and Control System to introduce the clean agent rapidly. This detection system is used to actuate a single, fixed fire suppression or alarm system based on inputs received from fire detection devices. The detection circuits can be configured using cross, counting, independent or priority-zone concepts.

Both automatic and manual actuators are available for release of the agent into the hazard area through fixed piping and nozzles. Seven nozzle sizes are available to provide the correct flow of agent in either 180 or 360 horizontal discharge patterns. For large hazards, containers can be connected to a common manifold.

The HYGOOD FM-200 Piston Flow Clean Agent Fire Suppression System carries UL and ULC. The system can be designed to meet the requirements of NFPA 2001 with components approved to provide the highest quality fire suppression system.

**FM-200 is a trademark of Chemours Chemical Corporation.*